

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An organic electroluminescence element, comprising:
a first electrode layer;
a second electrode layer; and
at least one organic thin film layer containing an organic luminous layer
disposed between the first electrode layer and the second electrode layer,
the first electrode layer, the second electrode layer and the organic luminous
layer forming a cumulate body with a flat surface,
~~at least one of~~ the first and second electrode layers having slopes that are
arranged substantially around the flat surface,
~~the~~ at least one of the first and second electrode layers being formed on a
convex section, and
a light generated in the organic layer being reflected by the slope of the second
electrode layer and going out to the side of the first electrode layer.
2. (Currently Amended) An organic electroluminescence element comprising:
a first electrode layer;
a second electrode layer; and
at least one organic thin film layer containing an organic luminous layer
disposed between the first electrode layer and the second electrode layer,
the first electrode layer, the second electrode layer and the organic luminous
layer forming a cumulate body with a flat surface,
~~at least one of~~ the first and second electrode layers having slopes that are
arranged substantially around the flat surface,

the slopes being formed on rim sides of a pixel, and

the slopes falling outwardly from a pixel region.

3. (Previously Presented) The organic electroluminescence element according to claim 1, the slopes being disposed such that a protruding height of the organic luminous layer is larger than a thickness of the organic luminous layer.

4. (Previously Presented) The organic electroluminescence element according to claim 1, the slopes being disposed such that a protruding height of the organic luminous layer by the slopes is larger than a total value of a thickness of the first electrode layer and a thickness of the organic luminous layer, or a total value of a thickness of the second electrode layer and the thickness of the of the organic luminous layer.

5. (Previously Presented) The organic electroluminescence element according to claim 1, the slopes including multiple slopes that are uniformly arranged.

6. (Previously Presented) The organic electroluminescence element according to claim 1, the slopes being formed by providing a projection, made of an insulating material, on a substrate forming a cumulate body of the organic electroluminescence element.

7. (Previously Presented) The organic electroluminescence element according to claim 1, the slopes being defined by forming projections on at least one of the first electrode layer and the second electrode layer, the projections corresponding to the slopes.

8-11. (Canceled)

12. (Previously Presented) The organic electroluminescent element according to claim 1,

the first electrode layer being light-transmissive, and the second electrode having light-reflectivity.

13-15. (Canceled)

16. (Previously Presented) An organic electroluminescent display comprising the organic electroluminescent element according to claim 1.

17-18. (Canceled)

19. (Previously Presented) The organic electroluminescent element according to claim 1,

the first electrode layer being an anode layer, and the second electrode layer being a cathode layer.

20-22. (Canceled)